



enoline 4 SMART

NEW “ENTRY LEVEL” LINE WHICH COMBINES THE BASIC FUNCTIONALITIES OF THE ENOMATIC® TECHNOLOGY WITH A COMPACT AND MODERN DESIGN. USER-FRIENDLY SYSTEM PARTICULARLY SUITABLE FOR SMALL INSTALLATIONS, TODAY AVAILABLE ALSO WITH “SUPERCOOL” REFRIGERATION.

enoline

- **Available models:**
(4 bottles in a row)
- enoline 4 Smart REF
- enoline 4 Smart SC
- **Serving temperature:**
- refrigerated: from 7 to 18 °C (from 45 to 64 °F)
- supercool: from 0 to 18 °C (from 32 to 64 °F)
- **Use and system activation:** behind the counter (without wine card) only.
- **Gas supply:** food grade nitrogen or argon (cylinder or generator not included).
- **Servings:** 3 volumes (touch-sensing functionality). Multiple supply option (the dispenser supplies from two taps simultaneously).
- **Materials:** stainless steel with baydur black polyurethane side inserts.
- **Cooling system:** by refrigerator compressor.
- **Condensation drainage:** not required.
- **Compressor positioning:** right or left side.
- **Lighting:** with double LED (static light).
- **Opening:** drop-down door with serigraphic glass and key lock.
- **Bottles lifting system:** pneumatic pistons which can be operated with air, nitrogen or argon.
- **Positioning:** can be lined up on both sides; 10 cm at rear and 25 cm on the top needed; support furniture needed.

model	L	H	D	weight	electrical requirements
enoline 4 smart REF	75 cm (29.6")	63 cm (24.8")	26 cm (10.3")	42 kg (92,6 lbs)	115 or 230 V 150 W
new enoline 4 smart SC	75 cm (29.6")	63 cm (24.8")	26 cm (10.3")	42 kg (92,6 lbs)	115 or 230 V 150 W